

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/22/2013 : Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures

Trade name : Petra Non-Chlorinated Brake Part Cleaner Non-VOC Compliant 12/15 oz

Product code : PETRA6001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Follow Label Directions

1.3. Details of the supplier of the safety data sheet

Petra Oil Company

6100 West by Northwest Blvd. Ste. 190

Houston, TX 77040

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Flam. Liq. 2 H225 Acute Tox. 1 (Oral) H300 Skin Irrit. 2 H315 Eye Dam. 1 H318 Repr. 1B H360 STOT SE 1 H370 STOT SE 3 H336 STOT RE 2 H373

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

GHS05







Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol

H225 - Highly flammable liquid and vapor

H300 - Fatal if swallowed H315 - Causes skin irritation

H318 - Causes serious eye damage H336 - May cause drowsiness or dizziness H360 - May damage fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting/... equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe dust/fume/gas/mist/vapors/spray P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash ... thoroughly after handling

P270 - Do no eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

21/06/2013 EN (English US) 1/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 - IF exposed or concerned: Get medical advice/attention

P310 - Immediately call a POISON CENTER/doctor/...
P312 - Call a POISON CENTER/doctor/.../if you feel unwell
P314 - Get medical advice and attention if you feel unwell

P321 - Specific treatment (see ... on this label)

P330 - If swallowed, rinse mouth

P332+P313 - If skin irritation occurs: Get medical advice/attention

P362 - Take off contaminated clothing

P370+P378 - In case of fire: Use ... for extinction

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50

P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification (GHS-US)
toluene	(CAS No) 108-88-3	30 - 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
methanol	(CAS No) 67-56-1	30 - 50	Flam. Liq. 2, H225 Acute Tox. 1 (Oral), H300 Eye Dam. 1, H318 Repr. 1B, H360 STOT SE 1, H370
acetone	(CAS No) 67-64-1	>= 24.357564	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
carbon dioxide, liquefied, under pressure	(CAS No) 124-38-9	5 - 10	Compressed gas, H280
benzene	(CAS No) 71-43-2	<= 0.002436	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician. Specific treatment (see ... on this

label).

First-aid measures after inhalation : Cough. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs:

Get medical advice/attention. Specific treatment (see ... on this label).

First-aid measures after eye contact : Direct contact with the eyes is likely to be irritating. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see ... on this label).

21/06/2013 EN (English US) 2/11

OZ

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. May damage fertility or the unborn child.

Causes damage to organs.

Symptoms/injuries after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Fatal if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Highly flammable liquid and vapor.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns

and injuries. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Avoid (reject) fire-fighting water to enter environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol level 3.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn,

even after use. Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. No naked lights. No smoking. Use only non-sparking tools. Do not handle until all safety precautions have been read and

understood. Obtain special instructions before use. Avoid breathing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Do not breathe

dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash ... thoroughly after handling. Do no eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/...

equipment.

21/06/2013 EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

temperatures exceeding 50°C/ 122°F. Keep in firepro of place. Keep container tightly closed.

Incompatible products : Strong bases. strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

3.1. Control parameters

methanol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm

toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm

carbon dioxide, liquefied, under pressure (124-38-9)		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (ppm)	30000 ppm

benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA ACGIH	ACGIH STEL (ppm)	2.5 ppm

acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA OSHA	OSHA PEL (STEL) (mg/m3)	2400 mg/m³

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosols.

Color : Colourless to light yellow.

Odor : Mild.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : < -78.9 °C Freezing point : No data available

Flash point : -29 °C Closed cup

Self ignition temperature : 385 $^{\circ}$

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available

21/06/2013 EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20 ℃ : No data available Relative density : 0.82 Solubility : Water: 64 % Log Pow : No data available Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidizing properties : No data available Explosive limits : 2.5 - 12.8 vol %

9.2. Other information

VOC content : 70.1 %
Gas group : Liquefied gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Fatal if swallowed.

methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (1187-2769 mg/kg bodyweight; Rat; Rat)
LD50 dermal rabbit	15800 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat)

toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg (5580 mg/kg bodyweight; Rat; Rat; Experimental value)
LD50 dermal rabbit 12223 mg/kg (>5000 mg/kg bodyweight; Rabbit; Experimental value; Other,>5000 mg/kg bodyweight; Rabbit; Experimental value; Other)	
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat)

benzene (71-43-2)	
LD50 oral rat	> 930 mg/kg (Rat)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	45 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat)

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Experimental value, Rat; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value, Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	71 mg/l/4h (76 mg/l/4h; Rat; Rat; Experimental value; Experimental value, 76 mg/l/4h; Rat; Rat; Experimental value; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value, Rat; Experimental value)
Skin corrosion/irritation	: Causes skin irritation.

21/06/2013 EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classifiedBased on available data, the classification criteria are not met

Carcinogenicity : Not classified

toluene (108-88-3)	
IARC group	3

benzene (71-43-2)	
IARC group	1

Reproductive toxicity : May damage fertility or the unborn child. Based on available data, the classification criteria are

not met

Specific target organ toxicity (single exposure) Causes damage to organs. May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

: May cause damage to organs through prolonged or repeated exposure.Based on available data,

the classification criteria are not met

Aspiration hazard Not classifiedBased on available data, the classification criteria are not met

Potential Adverse human health effects and

symptoms

: Fatal if swallowed.

Symptoms/injuries after inhalation Shortness of breath. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact Causes skin irritation.

Symptoms/injuries after eye contact Causes serious eye damage.

Symptoms/injuries after ingestion : Fatal if swallowed.

SECTION 12: Ecological information

Toxicity

methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; LETHAL)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; LETHAL)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)

toluene (108-88-3)	
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; LOCOMOTOR EFFECT)
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; TOXICITY TEST)
Threshold limit algae 2	105 mg/l (192 h: Microcystis aeruginosa)

carbon dioxide, liquefied, under pressure (124-38-9)	
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); LETHAL)
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); LETHAL)

benzene (71-43-2)	
LC50 fish 1	5.3 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	18 mg/l (24 h; Daphnia magna)
EC50 other aquatic organisms 1	29 mg/l (72 h; Selenastrum capricornutum)
LC50 fish 2	15.1 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 2	10 mg/l (48 h; Daphnia magna)
TLM fish 1	22.5 mg/l (96 h; Lepomis macrochirus; SOFT WATER)
TLM fish 2	32 mg/l (96 h; Pimephales promelas; HARD WATER)
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 2	50 mg/l (24 h; Phaeodactylum; PHOTOSYNTHESIS)

acetone (67-64-1)	
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; NOMINAL CONCENTRATION)
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)

21/06/2013 EN (English US) 6/11

Safety Data Sheet

BCF other aquatic organisms 2

Log Pow

acetone (67-64-1)	
TLM fish 1	13000 ppm (96 h; Gambusia affinis; TURBULENT WATER)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; PH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)
2.2. Persistence and degradability	
Petra Non-Chlorinated Brake Part Cleaner	Non-VOC Compliant 12/15 oz
Persistence and degradability	Not established.
·	Tot ostabiolica.
methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O²/g substance
Chemical oxygen demand (COD)	1.42 g O²/g substance
ThOD	1.5 g O²/g substance
BOD (% of ThOD)	0.40 - 0.73 % ThOD
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in so
Biochemical oxygen demand (BOD)	2.15 g O ² /g substance
Chemical oxygen demand (COD)	2.52 g O ² /g substance
ThOD	3.13 g O ² /g substance
BOD (% of ThOD)	0.69 % ThOD
carbon dioxide, liquefied, under pressure (124-38-9)
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
benzene (71-43-2)	•
Persistence and degradability	Biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in
r ersistence and degradability	soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	2.18 g O²/g substance
Chemical oxygen demand (COD)	2.15 g O²/g substance
ThOD	3.10 g O ² /g substance
BOD (% of ThOD)	0.70 % ThOD
acetone (67-64-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under
r disistence and degradability	anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.43 g O ² /g substance
Chemical oxygen demand (COD)	1.92 g O²/g substance
ThOD	2.20 g O²/g substance
2.3. Bioaccumulative potential	
<u> </u>	Non VOC Compliant 12/15 or
Petra Non-Chlorinated Brake Part Cleaner Bioaccumulative potential	Not established.
bioaccumulative potential	140t established.
methanol (67-56-1)	
BCF fish 1	< 10 (Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other, Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
toluene (108-88-3)	
BCF fish 1	13.2 (Anguilla japonica)
	13.2 (Anguilla japonica) 90 (72 h; Leuciscus idus)
BCF fish 1 BCF fish 2 BCF other aquatic organisms 1	

21/06/2013 EN (English US) 7/11

2.73 (Experimental value; Other; 20 °C, Experimental value; Other; 20 °C, Experimental value; Other; 20 °C)

4.2 (Mytilus edulis; FRESH WEIGHT)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Coruling to Federal Register / Vol. 77, No. 36 / Wiorday, Warch 20, 2012 / Rules and Regulations	
toluene (108-88-3)	
Low potential for bioaccumulation (BCF < 500).	
e (124-38-9)	
0.83 (Experimental value)	
Low potential for bioaccumulation (Log Kow < 4).	
19 Salmo gairdneri (Oncorhynchus mykiss)	
30 (24 h; Chlorella sp.; FRESH WEIGHT)	
2.13 (Experimental value)	
Low potential for bioaccumulation (BCF < 500).	
0.69 (Pisces)	
3	
-0.24 (Test data)	
Not bioaccumulative.	
methanol (67-56-1)	
0.023 N/m (20 ℃)	
0.03 N/m (20 ℃)	

acetone	(67-64-1)	
0		Ī

benzene (71-43-2)

Surface tension

Surface tension 0.0237 N/m

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to ...

Additional information : Flammable vapors may accumulate in the container. Handle empty containers with care because

residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

0.029 N/m (20 °C)

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2, Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosol

flammable, (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard

Classes

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gases



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

21/06/2013 EN (English US) 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Class (ADR) : 2 - Gases
Classification code (ADR) : 5TF

Danger labels (ADR) : 2.1 - Flammable gases

6.1 - Toxic substances



Tunnel restriction code : D
Excepted quantities (ADR) : E0

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Limited quantities (IMDG) : Aerosol can

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

Listed on the Canadian DSL (Domestic Substances List) inventory.

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Petra Non-Chlorinated Brake Part Cleaner Non-VOC Compliant 12/15 oz	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard

methanol (67-56-1)	
Listed on SARA Section 302 (Specific toxic chem	ical listings)
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard

acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard

15.2. International regulations

CANADA

Petra Non-Chlorinated Brake Part Cleaner Non-VOC Compliant 12/15 oz	
WHMIS Classification	Class B Division 5 - Flammable Aerosol Class D Division 2 Subdivision B - Toxic material causing other toxic effects
methanol (67-56-1)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
acetone (67-64-1)	

21/06/2013 EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- EEC Directive 79/831, sixth Amendment of the directive 67/548 (dangerous substances).

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Repr.Cat.3; R63

F; R11

T; R23/24/25

T; R39/23/24/25

Xn; R65

Xn; R48/20

Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

acetone (67-64-1)

Listed on Inventory of Chemicals and Chemical Substances (PICCS)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on KECI (Chemical Inventory of Korea)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on the Korean ECL (Existing Chemical List) inventory.

15.3. US State regulations

No additional information available

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : NFPA Aerosol Level 3. None.

Full text of H-phrases: see section 16:

Acute Tox. 1 (Oral)	Acute toxicity (oral) Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 2	Flammable liquids Category 2
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H300	Fatal if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer

21/06/2013 EN (English US) 10/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt


medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012) - Technical Chemical

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

21/06/2013 EN (English US) 11/11